







Acrow Cup Lock System

ACROW MISR Provides Full Site Service Based On More Than 35 Years Experience In The Field









Introduction	2
Advantages	3
Features	4
Cup Lock Standards Loading	6
Application	7
Componants	10





Introduction

Being one of the largest formwork and scaffolding companies, we are introducing the Cuplock system. It is a complete system that provides access scaffolding and formwork slab support. This formwork slab support can be used in a wide variety of applications from light to heavy duty scaffolding and shoring for buildings and other civil engineering work. In addition, no loose fittings are required. A hammer

is the only tool required for erection and dismantling of the system. Several accessories ensure the adaptability of the system to a wide variety of applications.







Advantages

- •It can be used for both scaffolding and shoring systems.
- •Minimum supervision is required since the system is rapidly erected and dismantled using the interlocking components which are rigidly secured with two cups. Simply hammered with no need for spanners.
- •Due to the lightness of the system

components, all can be easily handled by one man.

- •Ledgers are non-load bearing and can therefore be assembled at handrail height on external faces of independent scaffolding, thus offering the additional safety of handrails at all working levels.
- •Working levels can be changed

speedily and simply without disturbing the main structure of the scaffold.

•Cup-lock system components are manufactured from high quality tube having the same outside diameter as the traditional scaffold tube to facilitate tying scaffold to the building.












Features

The standard is the vertical member of cup lock system. It is made from high grade steel tube with outer diameter of 48.3 mm and thickness of 3.2 mm.

1- Standards

A series of bottom cups are welded at nominal 500 mm centers and free top cup to ensure providing a safe connection at any direction for the horizontal ledger attachment. Cup-lock sizes vary from 0.5 m to 3.0 m.





Features

2 -Ledger

The ledger is the horizontal member used to connect the standards in both the longitudinal and transversal directions. It is made of the same vertical tube.

They are welded together to blade the ends and fit in the bottom cup located in the standard.

Ledger sizes vary from 0.6 m to 2.4 m.



0.9m

1.2m

1.5m

1.8m

2.1m ⊨

2.4m ⊨




Cup lock standards loadings

Technical Data

•Restrained From 2 Directions



Restrained From 4 Directions






Application

Cup lock can be applied on the following:

- Early striking system using Cup lock verticals & ledgers, drop heads, decking and infill beams.
- •Cup lock and Timber beams.
- •Cup lock scaffolding.
- •Cup lock staircase.



Early striking system




Cup Lock and Timber beams



Applications


•Cup lock scaffolding





Applications

•Cup lock staircase





Item	Description	Code no.	Weight (kg)
	Cup lock vertical 3.00m 2.50m 2.00m 1.50m 1.00m 0.50m	6221177056070 6221177056063 6221177056056 6221177056049 6221177056032 6221177056025	10.86 9.05 7.25 5.45 3.65 1.825
	Cuplock ledger 2.40m 2.10m 1.80m 1.50m 1.20m 0.90m	6221177056018 6221177056001 6221177055998 6221177055981 6221177055974 6221177055967	8.34 7.33 6.33 5.32 4.32 3.31
	Cuplock cantiliver bracket 1.20/1.50 m	6221177045050	22.0



Item	Description	Code no.	Weight (kg)
	Scaffolding Tube ,L=1.00 m Scaffolding Tube,L=1.50 m Scaffolding Tube,L=2.00 m Scaffolding Tube,L=2.50 m Scaffolding Tube,L=3.00 m Scaffolding Tube,L=3.50 m Scaffolding Tube,L=4.00 m Scaffolding Tube,L=4.50 m Scaffolding Tube,L=5.00 m Scaffolding Tube,L=6.00 m	6221177017354 6221177017385 6221177017392 6221177017415 6221177017422 6221177017439 6221177017446 6221177017453 6221177017552	2.85 4.25 5.70 7.25 8.50 9.95 11.40 12.85 15.65 17.10
	Drop head 4-Sides	6221177008970	5.74
	Decking Beam , L =0.9 M Decking Beam , L =1.2 M Decking Beam , L =1.5 M Decking Beam , L =1.8 M Decking Beam , L =2.10 M Decking Beam , L =2.4 M	6221177008673 6221177008680 6221177008697 6221177008703 6221177008710 6221177008727	13.25 14.50 15.30 16.65 22.35 23.75



Item	Description	Code no.	Weight (kg)
	Infill Beam , L =0.60 M Infill Beam , L =0.90 M Infill Beam , L =1.2 M Infill Beam , L =1.50 M Infill Beam , L =1.80 M	6221177010508 6221177010515 6221177010522 6221177010539 6221177010546	1.90 2.95 3.80 4.80 5.75
4D 800	Timber H20 L = 2.50 m Timber H20 L = 2.90 m Timber H20 L = 3.30 m Timber H20 L = 3.60 m Timber H20 L = 3.90 m Timber H20 L = 4.50 m Timber H20 L = 4.90 m Timber H20 L = 5.90 m	6221177024062 6221177024076 6221177024093 6221177024109 6221177024116 6221177024130 6221177024147 6221177024154	11.25 13.00 14.85 16.20 17.55 20.22 22.05 26.55
	Acrow U-Head Jack Solid	6221177025922	7.40
	Post Head Jack Solid 34mm (H)	6221177013097	7.10



ltem	Description	Code no.	Weight (kg)
	Plain Base	6221177000851	1.40
	pressed Prop double Coupler	6221177006969	1.40
	presed Prop swivel Coupler	6221177006976	1.25







Acrow H20 & solider

Acrow One shutter solider



Acrow V.M.C



Acrow Tech-Form



Acrow Cuplock



Acrow Bridge table form



Acrow Circular column



Acrow climbing system



Acrow shorbrace Table form



Acrow Big steel panel



Acrow European prop



Acrow Vari form



Acrow Prop table form



Acrow frame



Acrow early striking system



Acrow Ring lock

www.acrow.co

20 OFFICE

AFRICA

EGYPT

Head Quarter

Factory: Wady Houf, Helwan Tel.: [+202] 23690 616 / 23690 739 [+202] 23695 700 / 23699 976

Fax: [+202] 23695 260 E-mail: info@acrow.co Alexandria Branch

27 Dr. mahmoud Daoud st. Tel.: [+203] 4200 289 E-mail: acrowalex@acrow.co

MOROCCO

221 BVD Zerktouni , 3ème et 4ème etage - B.N. 06/08, Casablanca 20100, Morocco

Tel. : [+212] 522 945 912 Mob. : [+212] 660 675 640 E-mail: acrowmorocco@acrow.co

ALGERIA

Siege Social, cité des travailleurs lot. 09 groupe 02 Dar El beida, Algiers

Tel.: +213 (0) 23 74 74 37
Tel.: +213 (0) 23 74 74 35
Fax: +213 (0) 23 74 74 37
E-mail: acrow-dz@acrow.co

NIGERIA

Block D, Plot 23, Water Corporation

drive, VI, Lagos.

Tel. : [+234] 818 0000 295 Mob. : [+234] 6061 7290 99 Email : acrownigeria@acrow.co

KENYA

Nairobi

Kiungani Rd, off Mombasa Rd, Nairobi, Kenya

Tel. : [+254] 772324535 E-mail: acrowkenya@acrow.co

TANZANIA

Dar EsSalam

Oyster Bay Masaki, Dar EsSalam Tel. : [+255] 768 696 314 E-mail: acrowtanzania@acrow.co 14

BRANCH

ASIA

KSA

Riyadh Office

Office No. 13A- Sultan Business Building - Almaathar Ash shamali district - Sultan Ben Abdulaziz Street - Riyadh

Tel. : [+966] 11 216 0504 Fax : [+966] 11 216 0503 Mob. : [+966] 55 001 2693 E-mail: acrowriyadh@acrow.co

Jeddah Office

Office No. 15 - 4th Floor - Zahid Building - Alsalamah district - Mohamed Ibrahim Masoud Street - Jeddah

Tel. : [+966] 12 691 7941 Fax : [+966] 12 275 1037 Mob. : [+966] 50 001 3206 E-mail: acrowjeddah@acrow.co

Dammam Office

Office 2, Alsalam Building, Madinat Alummal Dist., King Fahd Road Tel. : [+966] 13 805 4151 Fax : [+966] 11 216 0503 Mob. : [+966] 55 468 7057 E-mail: dammam@acrow.co

Madinah Al Munawwarah

Office 6, First Floor, Ghos Building, In Front Of Saudi Post, Sultanah Street, Almadinah

Tel. : [+966] 11 216 0504 Fax : [+966] 11 216 0503 Mob. : [+966] 55 775 8197 E-mail: almadinah@acrow.co

Tabuk City

Al Muruj District

Prince Mamdouh Bin Abdul Aziz Street Building Name : Tabuk Business Center Building No.2786

PO.Box: 47312

Second Floor, Office No.203

Tel.: [+966] 11 216 0504

Fax: [+966] 11 216 0503

Mob.: [+966] 55 001 2693

E-mail: acrowriyadh@acrow.co

UAE

Dubai

Office 1002, The Onyx Tower 2- The

greens - Dubai.

Tel. : [+971] 43439498 Fax : [+971] 43439598 Mob. : [+971] 528228811 E-mail: acrowgulf@acrow.co

Abu Dhabi

Office 816, Al Junaibi Tower, Al Muroor

Road - Abu Dhabi.

Mob.: [+971] 588113383 E-mail: acrowad@acrow.co



KUWAIT

Al Aridiyah , Block 2 , Building 92, Kuwait Khalid Ali Al Kharafi &

Tel.: [+965] 22083000 - Ext [240] **Fax:** [+965] 22083001

E-mail: acrowkuwait@acrow.co

OMAN

Acrow LLC

Office 23, Bin Hayl 2 Building , Bawshar St ,Muscat , Sultanate of Oman

Tel. : [+968] 24 112 791 Mob. : [+968] 92 543 734 E-mail: acrowmuscat@acrow.co

BAHRAIN

Acrow Bahrain Co. W.L.L

Office 1718, building 1260, Road 2421 Block 324 , Juffair, Manama , Kingdom of Bahrain

Mob.: [+973] 35 176 860 E-mail: acrowbahrain@acrow.co

JORDAN

Jordan - Amman - Al Jandawil - Hosni Subar Str - Builiding no 05 - Third Floor

Mob.: [+962] 797 603 936 E-mail: acrow.jordan@acrow.co

QATAR

Acrow Qatar

Salwa Road, Red Tag building, 1st floor, Doha P.O. Box No.: 15104 Tel.: [+974] 44582357

Fax: [+974] 44582376 E-mail: acrowqatar@acrow.co